



7" Digital LCD + Touch Screen




Touch Screen



Video Call



IPTV & VoD



Advertisement



Photo Frame



PoE



- ◆ TI DaVinci chipset
- ◆ 300K CMOS sensor camera
- ◆ 7" 800x480 digital LCD, Touch screen
- ◆ H.264 and H.263 video codec
- ◆ Full-duplex speakerphone
- ◆ Online Advertisement
- ◆ 2xLAN, 1xUSB, 1xSD
- ◆ A/V out, Headset, PoE

מפרט טכני

Video Features

- ◆ Video codec's: H.264 , H.263
- ◆ Picture codec's: JPEG, GIF, PNG
- ◆ Maximum D1 30 fps
- ◆ Bandwidth level: 128kbps - 1Mbps
- ◆ Powerful video DSP with advanced AJC and PLC

Voice Features

- ◆ Voice codec's: G.711, G.723.1, G.726, G.729AB
- ◆ VAD, CNG, AEC, PLC, AJB, AGC
- ◆ Full-duplex hands-free speakerphone with AEC

Phone Features

- ◆ Video and voice call selection
- ◆ Call forward, call waiting, call transfer
- ◆ Hold, DND, mute, call pickup, auto answer
- ◆ Dial plan, dial-now, speed dial
- ◆ Caller ID display, call history
- ◆ Phonebook, contact group manage
- ◆ Volume adjustment, ring tone selection
- ◆ Wall paper, screen saver, sleep
- ◆ Get date & time manually or automatically
- ◆ Icon-driven menu
- ◆ Multi-language

Network Features

- ◆ SIP v1(RFC2543), v2(RFC3261)
- ◆ NAT transverse: STUN mode
- ◆ IP assignment: static/DHCP/PPPoE
- ◆ In-Band DTMF, Out-of-Band DTMF, SIP Info
- ◆ Proxy mode and peer-to-peer SIP link mode
- ◆ TFTP/DHCP/PPPoE client
- ◆ NAT/DHCP server
- ◆ HTTP web server
- ◆ DNS client
- ◆ SNTP
- ◆ QoS, VLAN (pending)

Management

- ◆ FTP/TFTP/HTTP/PnP auto-provision
- ◆ Configuration: browser/phone/ auto-provision
- ◆ TR069 optional

Video Application

- ◆ Online/offline advertisement
- ◆ Color media ring
- ◆ Picture slide show support
- ◆ Picture-in-Picture (PIP)
- ◆ Camera block
- ◆ Video phone book
- ◆ Digital photo frame

physical Features

- ◆ TI DaVinci chipset
- ◆ 128MB flash and 128MB DDR2 memory
- ◆ 7" large digital TFT-LCD with 800x480 pixels
- ◆ Touch screen
- ◆ Camera: adjustable 300K pixels CMOS sensor
- ◆ A/V out: RCA style stereo audio and composite video output
- ◆ 2xRJ45 Ethernet 10/100M ports
- ◆ 1xSD slot
- ◆ 1xUSB 2.0 port
- ◆ 2.5mm headset port
- ◆ Power over Ethernet (IEEE 802.3af)

Security

- ◆ Digest authentication using MD5/MD5-sess
- ◆ Secure configuration file via AES encryption
- ◆ Admin/user configuration mode